

		Track	Homestead RC Raceway		Clutch settings		Front shocks		Front anti roll bar		Engine		
		Layout	technical <input type="radio"/>	mixed <input checked="" type="radio"/>	fast <input type="radio"/>	Shoe	standard <input checked="" type="radio"/>	optional <input type="radio"/>	Piston	1	<input type="radio"/> <input type="radio"/> <input checked="" type="radio"/> <input type="radio"/> <input type="radio"/>	Type	Flash21PTS
Date	4.16.2011	Traction	low <input type="radio"/>	medium <input checked="" type="radio"/>	high <input type="radio"/>	Bell clearance (mm)	0.6	Oil	400	<input type="radio"/> <input type="radio"/> <input checked="" type="radio"/> <input type="radio"/> <input type="radio"/>	Plug	8TF	
		Temperature	air: ap. 35°	track:		Spring	New	Spring	Yellow	Servosaver position	Manifold	Short	
Driver	Robert Pietsch	Pinion	1st: 16	2nd: 20	Bell axial play (mm)	0.1	Rear shocks			Pipe	2015		
		Spur	1st: 50	2nd: 46	Body		Piston	2		Tires			
Race	Worlds Miami	Pulley	28 <input type="radio"/>	29 <input checked="" type="radio"/>	Type	P909	Oil	500		Front	inside outside Contact 32		
		Clutch	standard <input type="radio"/>	optional <input checked="" type="radio"/>	Wing position (mm)	10	Spring	Grey		Rear	inside outside Contact 35		

