

		Track	Homestead RC Raceway		Clutch settings		Front shocks		Front anti roll bar		Engine		
		Layout	technical <input type="radio"/>	mixed <input checked="" type="radio"/>	fast <input type="radio"/>	Shoe	standard <input checked="" type="radio"/>	optional <input type="radio"/>	Piston	1.3x1	<input checked="" type="radio"/> <input type="radio"/> <input type="radio"/> <input type="radio"/> <input type="radio"/>	Type	Flash21PTS
Date	4.16.2011	Traction	low <input type="radio"/> medium <input checked="" type="radio"/> high <input type="radio"/>		Bell clearance (mm)		0.7	Oil	600	<input checked="" type="radio"/> <input type="radio"/> <input type="radio"/> <input type="radio"/> <input type="radio"/>	Plug	8TGH	
		Temperature	air:	track:	Spring		New	Spring	Yellow	Servosaver position		Manifold	Medium
Driver	Shinya Shimazaki	Pinion	1st: 16	2nd: 20	Bell axial play (mm)		0.1	Rear shocks			Pipe	2015	
		Spur	1st: 48	2nd: 45	Body			Piston	1.1x2		Tires		
Race	Worlds Miami	Pulley	28 <input type="radio"/>	29 <input checked="" type="radio"/>	Type		P909	Oil	600		Front	inside outside ZAC 30	
		Clutch	standard <input type="radio"/>	optional <input checked="" type="radio"/>	Wing position (mm)		5	Spring	White		Rear	inside outside ZAC 35	

