



		Tires		Clutch settings		Front shocks		Engine						
Date/Track	Ettlingen 20.8.11	Front shore	left 37 / right 37	Shoe	std.	Piston	std. 2 hole	Type	Flash PTS					
Driver	R. Pietsch	Rear shore	left 40 / right 40	Bell clearance (mm)	0.5mm	Oil	400	Plug/Fuel	6tf / MLC					
Temp. °C.	air 34° / track ~50°	Front φ	left 60 / right 60	Spring	H0764	Spring	purple	Pipe/Manifold	Pipe 2660 / Manifold med.					
		Rear φ	left 62 / right 62	Bell axial play (mm)	0.1-0.2		Rear shocks		Gear ratio chart					
Track layout/traction	technical <input type="radio"/> low <input type="radio"/>	Differential		Gearing		Piston	std. 2 hole	Spur Pinion	1st 2nd					
	mixed <input type="radio"/> medium <input type="radio"/>	Front diff. oil cst.	300000	1st gear	15 / 53	Oil	400	14	52	53	54	47	48	49
	fast <input checked="" type="radio"/> high <input checked="" type="radio"/>	Rear diff. oil cst.	50000	2n gear	20 / 48	Spring	silver xray	15	7,614	7,761	7,907			
								19				5,071	5,179	5,278
								20				4,818	4,92	5,023
								21				4,588	4,686	4,783

