DRIVER: **Basic setup (ver.2601)**
DATE:
OUTSIDE TEMP. :
TRACK TEMP. :
REV.2601

TRACK:
SURFACE: ROUGH ○ SMOOTH ○
LAYOUT: TIGHT ○ MIXED ○ FAST ○
TRACTION: LOW ○ MID. ○ HIGH ○
RACE: RESULT:

TRANSMITTER:
RECEIVER:
ST.SERVO:
ST.EXPO:
ST.SPEED:

TH.SERVO:
TH.EXPO:
TH.SPEED:
1ST.GEAR PINION/SPUR:
2ND.GEAR PINION/SPUR:

TIRE:
TIRE SIZE(F/R):
ADDITIVE:
ADDITIVE TIME:

SHIM (mm) **3** UP ○ LOW ○
OFFSET **kit**
T2159(OPT.)
H0187(OPT.)
BUMPER KIT ○ HARD(OPT.) ○

WHEELBASE (0~-2mm) **-2**
CAMBER° **2**
TOE OUT° **1**
STEERING° (outside) **max.**
DOWNSTOP (mm) **1**
RIDE HEIGHT (mm) **8**
TRACK WIDTH (mm) **251**

LONG ↔ SHORT (8 / 9 / 10)
H2326 POS. F ○ R ○

ST.(mm) **19**
TH.(mm) **19**

H0555C ⟷ H0555D
H0555C/D/E - H2509 - H2510

H0555C		H0555D
SHIM (mm) **0**		SHIM (mm) **0**
kit	PISTON	**kit**
kit	SPRING	**kit**
kit	OIL#	**kit**
12.5	(mm)	**13.5**

2.2 ○ 2.3 ◉ 2.4 ○ — 2.8 ○ 2.9 ◉ 3.0 ○

1 (mm)
6 (mm)
CAMBER° **3**
TOE IN° **2.5**
DOWNSTOP(mm) **8.5**
RIDE HEIGHT (mm) **9**
TRACK WIDTH (mm) **260**

SHOCK POSITION
OFFSET **kit**
SHIM(mm) **4**
SHOCK POSITION
H2159-B ○ MID. ○
H2168 ○ LOW ○

CASTER (mm) **1**
SCREW USED ◉ NOT USED ○

ROD SHIM (mm) **1**
INSERT DOT POSITION
FRONT ○ REAR ◉

UP ◉ LOW ○

UP ○ LOW ◉

INSERT DOT POSITION
FRONT ○ REAR ○

A - ARM ◉
I - ARM ○
H2164 □

CAR OVERALL WEIGHT(g)
ADD. WEIGHTS(g):
BATTERY(g)
H2412(18g) □
BATTERY PLATE KIT(H2313) ◉ OPT. ○
WEIGHT BALANCE F/R ○○○○○○○

BUMPER WEIGHT (g)

CUTTED □

BODYSHELL & WING TYPE **Hyper Diablo**
DISTANCE TO BUMPER(mm) **8~9** (mm)
BODYSHELL WEIGHT(g)
6

NOTE:

FRONT ← — → REAR

MRX7
1/8TH SCALE 4WD NITRO POWERED RACE CAR