

DRIVER	Kit Std. Setup JP Asphalt		
DATE			
TRACK	Carpet <input type="radio"/>	Asphalt <input checked="" type="radio"/>	
TRACTION	LOW <input type="radio"/>	MEDIUM <input checked="" type="radio"/>	HIGH <input type="radio"/>
LAYOUT	SLOW <input type="radio"/>	MIXED <input checked="" type="radio"/>	FAST <input type="radio"/>
TEMP °C	AIR	TRACK	
ELECTRONICS			
ESC	ESC SET	MOTOR	
SERVO	RECEIVER	BATTERY	
TIRES			
BRAND	Rush/Yurugix		
TYPE	36S/40S		
ADDITIVE	NASA V3 Yellow		
WARMER °C	FRONT 60°	REAR	60°
TIME(min)	FRONT 5	REAR	5
SHOCK ABSORBERS			
PISTON	FRONT Std.	REAR	Std.
SHOCK CASE	Std.		Std.
OIL	350		350
SPRING	6.0P		6.75
LENGTH	9.5		10
ANTI ROLL BAR FRONT/REAR			
FRONT	1.2	REAR	1.1
DIFF	<input checked="" type="radio"/>	SPOOL	<input type="radio"/>
OIL CST	1.000K		
GEAR RATIO (T)Spur/(T)Pinion*1,9=Ratio			
PINION		SPUR	
AERODYNAMIC SETTINGS			
BODY TYPE			
WING TYPE			
WING POS	(mm)		
BODY POSITION (see picture below)	(mm) horizontal		
FRONT BODY HEIGHT & POSITION	REAR BODY POST A2407C	<input type="radio"/>	REAR BODY POST A2416B
(mm) vertical	(mm)		(mm)

STEERING LIMITER

A2304 (5mm)

A2305 (5.5mm)

A2306 (6mm)

STEERING ANGLE IN°

STEERING ANGLE OUT°

16

A2427 USED

YES

NO

A2427 SHIM(mm)

Std.

UPPER ARM POS. FR(mm)

1.5

SHOCK POS (mm)

0

UPPER ARM POS. FF(mm)

1.5

LOWER ARM POS. FR(mm)

1

FF(mm)

1

STEERING ROD POS (mm)

4

SHIM UPRIGHT T (mm)

2

SHIM UPRIGHT L (mm)

0

UPPERARM POS. (CASTER)

REAR/5°

FRONT/4°

CAMBER/°

2

TOE OUT/°

1

OFFSET (mm)

4

RIDE HEIGHT(mm)

5.1

DOWNSTOP(mm)

6.0

FRONT

ACKERMANN SHIM (mm)

0

SHIM S HORN (mm)

0.5

LENGTH S HORN (mm)

17

A2529 POSITION

INSIDE

OUTSIDE

A2530 POSITION

INSIDE

OUTSIDE

REAR TOE ROD POS

FRONT

REAR

UPPERARM POS. (CASTER)

FRONT/-4°

REAR/-3°

SHIM UPRIGHT T (mm)

3

CAMBER/°

2

TOE IN/°

4/5

OFFSET (mm)

4.5

RIDE HEIGHT(mm)

5.1

DOWNSTOP(mm)

5.8

REAR

BATTERY POSITION

A2430(40g)

A2432(85g)

A2419

A2419 SCREW

MM SCREW

A

E

WEIGHT POSITIONS (g)

FRONT/REAR WEIGHT DISTRIBUTION HOLE#

SHOCK TOWER

BELT TENSION

2

1pc. UPPERDECK TYPE

2.0

OVERALL WEIGHT(g)

UPPERDECK SCREW

UPPERDECK BEARING

2pc. UPPERDECK

FRONT SCREWS

REAR SCREWS

A2524F A2542

A2524R A2543

A2158

FRONT (BULKHEAD)

FRONT (2pc.UPPERDECK)

REAR (UPPERDECK)

REMARKS